



Phone: 602.635.4480

Email: [steve@srcsurplus.com](mailto:steve@srcsurplus.com)

## Test Equity 1007C Environmental Test Chamber Cascade

7cuft Programmable Cascade Environmental Chamber  
Temperature Range: -75C +175C | Voltage: 208 / 1 phase



Larger Image Test Equity  
Environmental Test Chamber

Larger Image Test Equity Environmental Chamber

### Test Equity 1007C Environmental Temperature Chamber Specification

- -73°C to +175°C Temperature Range (opt. to +205°C)
- 7 Cu Ft Workspace, 24 W x 21 H x 24 D (198 Liters)
- Watlow F4 Programmable Temperature Controller
- Watlow 97 High / Low Limit Control & Alarm
- Viewing Window & Interior Light
- 4" Access Ports
  - Left Side
  - Right Side
- Non-CFC Cascade Refrigeration

### Test Equity 1007C Environmental Test Chamber Controller Package:

- **Watlow F4 Programmable Temperature Controller:**  
Up to 256 steps can be programmed into as many as 40 namable profiles. The context sensitive information key and guided steps make profile programming fast and easy. A four-line backlit LCD displays programming, setup, operating and help information. A large LED readout indicates the actual chamber temperature with 0.1° resolution
- **Watlow 97 High/Low Temperature Limit Controller & Alarm:**  
Provides independent protection against excess temperatures. Both high and low limits can be set. The upper LED readout indicates the actual chamber temperature while the lower readout indicates the status. The limit controller will shut down the chamber and trigger the audible alarm in the event of an out of limit condition.