

## Thermotron HPS-16 Fast Ramp Environmental Temperature Test Chamber



### Thermotron Environmental Temperature Test Chamber Model HPS 16 Description:

- Temperature Range:
  - -73 °C to 177 °C ( -100 °F to 350 °F )
- Temperature Tolerance:
  - +/- 1.1°C once chamber is stable
- Chamber Volume:
  - 16 cuft
- Interior Dimensions:
  - 30" W x 30" H x 31" D
- Compressors:
  - Air Cooled *no need for facility chilled water (H2O)*

### Thermotron 7800 Programming Controller

The Thermotron 7800 is a microprocessor-based programmer & controller. The programmer function allow you to program temperature, temperature | humidity, or other types of profile tests & store them in the program memory. You can use these programs to operate the controller functions of the 7800. Storage of up to 10 programs; factory-programmed standard IEC and MIL-STD profiles.

**Thermotron HPS Environmental Temperature Chamber to be refurbished & sold with a standard warranty. Please contact us for more information. 602.635.4480**

### [Environmental Test Chamber Refurbishment Information](#)

SRC Surplus makes no representation of any item sold to be fit for a particular purpose and assumes no liability for its use or misuse. It is assumed that the unit will be installed and operated by qualified personnel. Refunds are not issued on returns. Above specifications are for the current model, some specifications may vary slightly from the actual unit.